



AUDIO VISUAL ALARM

Size of the Dumper and other Heavy Earth Moving Machinery (H.E.M.M.) is, so big that it is impossible for the Operator to see the back side of the vehicle so that he could alert, any person, standing behind. Therefore in order to avoid accident, during reversing a safety device to alarm, with sound and visual indicator to the person, who is standing behind the vehicle, is needed.



Director General Mines Safety has also observed that the maximum number of fatal accidents occur during reversing of Surface Transport Machineries in open cast mines, and to reduce accidents vide their circular no. / 04 of 2008". made it compulsory to install Audio Visual Alarm in every H.E.M.M. & Surface Transportation Machineries used in Mines.

We, being a leading manufacturing organization for the safely products used in mines, has developed and manufactured an Audio Visual Alarm Model: AVA2010. This Audio Visual Alarm "AVA2010" meets all the standard and specification laid down by DGMS.

We hold the **ISO 9001:2015**, Quality Assurance Certificate for our product range.

As mentioned in Circular No. 1, our Audio Visual Alarm "AVA2010" has also tested and found satisfactory by the

| TECHNICAL SPECIFICATION: | |
|---------------------------------|---|
| AUDIO | Dual Pizo-Buzzer, while reversing, delivering Alarm of 110 dB (measured at a distance of 1.2 meter distance) Two buzzer are arranged in such a way that if any fault occurs in one buzzer other will work without any interface. |
| VISUAL | Bright focus type Red LED (24 nos. of 5 mm size) blinks continuously while reversing emitting uniform light of 350 Lux. brightness. |
| VOLTAGE | Operates ideally on 24 Volt D.C. and 12 Volt D.C. |
| CURRENT | The maximum Current consumption is 150 mA |
| PROTECTION | Tested as per IP 67 & as per DGMS Circular No. 01 of 2010. The electronic circuits and buzzers are totally sealed by epoxy resin, so that nothing can enter in it. Our Audio Visual Alarm is 100% Water Proof. It even works after totally immersed in water. It does not have free space to accumulate ingress dust/water into its enclose. |
| TIME | Only Start And Off When use Reverse Gear. |
| DIMENSION: | Length-154 mm, Height-82 mm and Depth-75 mm. |
| WEIGHT | 750 gms. approx. |
| ENCLOSURE | Polycarbonate and M.S. sheet |
| COLOR | Black powder coated, (Siemens Gray, Yellow, or as per requirement) |